

Christie AP Series

Boardrooms
Classrooms
Conference rooms



Christie performance, exceptional value

The Christie® AP Series comprises two feature-rich, 5000-lumen-class 3LCD projectors showcasing Christie's renowned level of performance in a compact, easy-to-use and value-added package.

Offering a long lamp life (up to 6000 hours) and integrated audio, the AP Series provides a low total cost of ownership and is designed for easy classroom or meeting space installation.

Featuring a comprehensive list of I/O connections, including HDBaseT, these projectors handle a variety of integration environments and content sources. With WXGA or WUXGA resolution and up to 10000:1 contrast ratio, images are crisp and clear, ensuring your presentation looks great in any setting.

CHRISTIE®



		Christie LW502 121-041106-01	Christie LWU502 121-042107-01
Image	brightness (lumens)	• Center - 5401 • ANSI - 5000 • ISO - 5525	• Center - 5309 • ANSI - 5000 • ISO - 5525
	contrast	• 5000:1	• 10,000:1
Display technology	type	• 3 x 0.59" Inorganic LCD	• 3 x 0.67" Inorganic LCD
	native resolution	• 1280 x 800 WXGA	• 1920 x 1200 WUXGA
Lamp	type	• 300W UHB	
	typical lifetime	• Normal mode: up to 4000 hrs • Eco mode: up to 6000 hrs	
Inputs	signals	• VGA/SVGA/XGA/WXGA/WXGA+/SXGA/SXGA+/WSXGA+/UXGA/WUXGA/MAC 16" • NTSC, NTSC4.43, PAL, PAL-M, PAL-N, SECAM • 480i, 480p, 576i, 720p, 1080i, 1080p	
	scan rates	• Horizontal: 15-106kHz • Vertical: 60-120Hz	
	standard	• Computer Input: 15-pin D-sub x 1 • Digital Input: HDMI x 2, HDBaseT x 1 • Video Input: Composite video RCA jack x 1, Component video 15-pin D-sub x 1 • Audio Input: 3.5mm stereo mini jack x 1, RCA jack (L/R) x 1 • USB Type A x 1 (for wireless network)	
Outputs		• HDMI x 1 • 15-pin D-sub x 1 • Audio output 3.5mm stereo mini jack x 1	
Control and networking		• 9-pin D-sub x 1 (RS-232C) • RJ-45 port (HDBaseT)	
Accessories	standard	• IR remote • AC line cords for projector head • RGB cable • Adapter cover • Lens covers • User documentation	
	optional	• Ceiling mount (108-506102-01) • 300W UHB lamp (003-005852-01) • Air filter (003-005853-01) • USB wireless adapter (121-116109-XX)	
Lens	adjustment	• Focus and lens shift	
	lens	• 1.65-2.15mm x 1.6 manual zoom	• 1.58-2.06 x 1.7 manual zoom
Power requirements	operating voltage	• 100-120 VAC @ 50/60Hz • 220-240 VAC @ 50/60Hz	
	power consumption	• 440W @ 100-120 VAC • 420W @ 220-240 VAC	
	operating current	• 4.4A @ 100 VAC • 2.2A @ 220 VAC	
	dissipation	• 1502 BTU/hr @ 100-120V • 1433 BTU/hr @ 220-240V	
Audible noise		• Standard mode: 39dB(A) • Eco mode: 30dB(A)	
Physical	size	• (LxWxH) 13.3 x 18.3 x 5.4" (338 x 466 x 138mm) w/o feet	
	shipping size	• (LxWxH) 18.8 x 22 x 9.7" (478 x 560 x 246mm)	
	weight	• 15.2lbs (6.9kg)	• 15.9lbs (7.2kg)
	shipping weight	• 21.8lbs (9.9kg)	• 22.7lbs (10.3kg)
Operating environment	temperature	• Temp: 40-104°F (5-40°C)	
	humidity	• Humidity: 10-85% non-condensing	
	altitude	• 0-10,000ft (3048m)	
Key features		• HDBaseT • Long-life lamp up to 6000 hrs (eco mode) • AMX and Crestron connectivity • Extron XTP certified • Hybrid filter up to 10,000 hrs • DICOM simulation mode • HDCR • Picture-in-Picture/Picture-by-Picture • Edge blending • Warping • Zoom, focus, H/V lens shift • HDMI-Out • Closed caption • Built-in keypad • 3D Keystone • Wireless capable	
Regulatory		• Directives: RoHS • REACH • WEEE • UL/CSA/IEC 60950-1 • FCC Class A • CE	
Warranty		• Three years on the projector • Contact an authorized Christie representative for full details of our limited warranty	

Christie support and services

All Christie products are backed by industry-leading warranties, renowned service and support. We ensure our customers are well supported with training, service and technical knowledge through our extensive distribution and support network.

Corporate offices

Christie Digital Systems USA, Inc.
Cypress
ph: 714 236 8610
Christie Digital Systems Canada Inc.
Kitchener
ph: 519 744 8005

Worldwide offices

Australia
ph: +61 (0) 7 3624 4888
Brazil
ph: +55 (11) 2548 4753
China (Beijing)
ph: +86 10 6561 0240
China (Shanghai)
ph: +86 21 6278 7708
France
ph: +33 (0) 1 41 21 44 04

Germany
ph: +49 2161 664540
India
ph: +91 (080) 6708 9999
Japan (Tokyo)
ph: 81 3 3599 7481
Korea (Seoul)
ph: +82 2 702 1601
Mexico
ph: +52 55-4744-1790

Republic of South Africa
ph: +27 11 251 0000
Russian Federation
and Eastern Europe
ph: +36 (0) 1 47 48 100
Singapore
ph: +65 6877 8737
Spain
ph: +34 91 633 9990
United Arab Emirates
ph: +971 4 3206688

United Kingdom
ph: +44 (0) 118 977 8000
United States (Arizona)
ph: 602 943 5700
United States (New York)
ph: 646 779 2014
**Independent sales
consultant offices**
Italy
ph: +39 (0) 2 9902 1161



For the most current specification information, please visit www.christiedigital.com

Copyright 2016 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4339 Aug16

CHRISTIE®